

MC100 GPIO

Terminal/Gateway

















The MC100 GPIO gateway is equipped with a wide range of analogue inputs and digital in- and outputs.

Node-RED™, a simple graphical programming interface supporting various pre-configured transmission protocols, can be used to forward measured values, meter readings, switching statuses and calculations to inhouse servers or visualization software via LTE mobile networks.

In many cases the MC100 GPIO can be used to replace an under-used but cost-intensive electrical PLC controller while simultaneously functioning as an IoT gateway in a single device.

Key features & functionalities:

- Programmable 4G LTE GPIO Terminal/Gateway
- Quectel EC21-E module integrated
- Out of the box ready for mobile Internet communication
- OpenWrt 21 based Linux distribution, Kernel 5.4.154, optimized for the ARM-based MC100 Gateway
- Node-RED™ – flow-based programming tool pre-installed
- Supports comprehensive cloud and server protocols
- Configuration via web interface
- Free programmable

 4G LTE	 Node-RED™	 OpenWrt Linux	 Cloud-Service	 8in/8out	 2out	 GPS/GNSS (optional)
 10/100 MBit/s Ethernet	 RS232*	 USB 2.0*	 RS485*	 CAN 2.0B*	 2in/2out*	 WLAN* (optional)

* only Gateway

MC100 GPIO Terminal/Gateway

Technical Data

General	Description	Terminal	Gateway
Type	Wireless 4G LTE gateway with GPIO interfaces	x	x
Dimensions (W x H x D)	120 x 75 x 35 mm	x	x
Weight	approx. 175 g	x	x
Supply voltage	8 to 30 V DC	x	x
Operation temperature	-20 °C to +70 °C	x	x
Housing	Plastic	x	x
Protection class	IP20	x	x
Mounting	Wall mounting (DIN rail adapter optional)	x	x
Wireless module embedded	Quectel EC21-E	x	x
Mobile			
Supporting networks	LTE Cat1: Bands: 1, 3, 5, 7, 8, 20 WCDMA: Bands: 1, 5, 8 GSM/GPRS/EDGE: Bands: 3, 8	x	x
Transmission rates LTE	Up to 5 Mbps uplink and 10 Mbps downlink	x	x
Transmission rates HSPA+	Up to 5.76 Mbps uplink and 42 Mbps downlink	x	x
Transmission rates WCDMA	Up to 384 kbps uplink and 384 kbps downlink	x	x
Transmission rates EDGE	Up to 236.8 kbps uplink and 296 kbps downlink	x	x
Transmission rates GPRS	Up to 85.6 kbps uplink and 107 kbps downlink	x	x
Antenna connections	SMA (female)	2	2
Controller, Memory and OS			
Controller	ARM Cortex-A7 NXP i.MX 6 UltraLite, 528 MHz	x	x
RAM	512 MB	x	x
Flash	4 GB	x	x
OS	OpenWrt Linux	x	x
Programmable	C/C++, Python™, Java™, Node-RED™ or others	x	x
Interfaces controller board (sides)			
Power	Plug-in screw-type terminal	1	1
Ethernet	10/100 MBit/s	1	1
RS232	DB9 (RX,TX,RTS,CTS)	-	1
RS485	Not galvanic isolated, plug-in screw-type terminal	-	1
USB	USB 2.0 Type A	-	1
Digital inputs	Galvanic isolated, special common GND (IGND), 0 - 30 V, threshold 6 V	-	2
Digital outputs	Galvanic isolated, special common GND (IGND), solid state relais, 300 mA max low-side-switch to IGND	-	2
CAN	CAN 2.0B, plug-in screw-type terminal	-	1
LED 1	Power	x	x
LED 2 and 3	Free programmable	x	x
LED 4	GSM	x	x
SIM	Mini SIM	x	x
SD card	Micro SD, up to 64 GB (internal)	x	x
GPS	GPS/GNSS (GLONASS/BeiDou/Galileo)	optional	optional
WLAN	802.11 b/g/n	-	optional
Interfaces extension board (top)			
Digital inputs	Galvanic isolated 0 - 30 V, threshold 6 V	8	8
Digital outputs	Galvanic isolated solid state relais, 300 mA max	8	8
Analog inputs current	0 - 20 mA	2/4	2/4
Analog inputs voltage	0 - 10 V	2/0	2/0
PWM outputs	low-side-switch to GND	2	2
Other properties			
Configurations	Basic configuration via web interface, SSH	x	x
RS232 console port	on RS232 interface	-	optional
Delivery includes			
Wall adapter	Plastic holder	x	x
Connectors	WR-TBL Series 361 - 3.81 mm vertical cable entry plug (Würth)	x	x
Printed documentation	Quick Guide	x	x

Mistakes and changes are reserved.

MC100 GPIO Terminal/Gateway

Variants / Accessories

Variants		Part-Number	
		Terminal	Gateway
MC100 GPIO	2 x 0-20 mA, 2 x 0-10 V	160490	162771
MC100 GPIO	4 x 0-20 mA	-	160481
MC100 GPIO with GPS	4 x 0-20 mA	162358	163167
MC100 GPIO with WLAN	4 x 0-20 mA	-	160484
MC100 GPIO with WLAN/GPS	4 x 0-20 mA	-	162736
Accessories		Part-Number	
Top-hat rail bracket KIT	for DIN rail mounting	100046	100046
Power supply / Mount Adapter EU	18 W AC/12 V DC 1,5A	100909	100909
Network cable	Cat. 5, 1 m	100810	100810
Data cable	Adapter cable for ASC1, RS232 (SuB D9, female) - 1m - 3pin plug	-	162500
MiMo wall antenna	GSM/UMTS/LTE, 2 m RG174, 2x SMA (male)	101268	101268
Portable antenna	GSM/UMTS/LTE, SMA (male)	101292	101292
GPS antenna	1575.42 MHz, 2 dBi, 3 m RG174 SMA (male), magnetic	101259	101259

Mistakes and changes are reserved.