

MC92

Terminal



The MC92 Terminal is suitable for use over LTE with fallback to UMTS, EDGE and GSM.

Using classical AT commands, e.g. sending of short messages via SMS, HTTP(S), MQTT or E-mails via SMTP can be accomplished.

Key features & functionalities:

- Terminal with mobile 4G LTE modem
- Quectel EC21-E module integrated
- Quectel Enhanced AT Commands
- Metal housing
- Industrial platform



4G LTE



RS232



USB 2.0
(optional)



GPS/GNSS
(optional)

MC92 Terminal

Technical Data

Product	MC92	
Model	Terminal	
General	Description	
Type	Wireless 4G LTE Cat 1 data terminal	x
Dimensions (W x H x D)	44 x 105 x 84 mm	x
Weight	approx. 270 g	x
Supply voltage	8 to 30 V DC	x
Operation temperature	-20 °C to +60 °C	x
Housing	Aluminium	x
Protection class	IP40	x
Mounting	Tabeltop / DIN rail	x
Wireless module embedded	Quectel EC21-E	x
Mobile		
Supporting networks	LTE FDD: Bands: 1, 3, 5, 7, 8, 20 HSDPA/HSUPA/HSPA+: Bands: 1, 5, 8, all bands with diversity GSM/GPRS/EDGE: Bands: 3, 8	x
Transmission rates LTE	Up to 5 Mbps uplink and 10 Mbps downlink	x
Transmission rates HSPA+	Up to 5.76 Mbps uplink and 21.6 Mbps downlink	x
Transmission rates EDGE	Up to 236.8 kbps uplink and 236.8 kbps downlink	x
Transmission rates GPRS	Up to 85.6 kbps uplink and 85.6 kbps downlink	x
Antenna connections	SMA (female)	1
Interfaces		
USB	USB 2.0 Type A	Optional
RS232	DB9 (RX, TX, RTS, CTS, DTR, DCD, RI)	x
Power	Plug-in screw-type terminal	x
LED NET	LTE (always on)	x
LED1-4	Switchable by AT commands	x
LED PWR	Power	x
GPS	GPS/GLONASS/BeiDou/Galileo	Optional
SIM	Mini SIM	x
Delivery includes	Description	
Top-hat rail holder	DIN rail	x
Printed documentation	Quick Guide	x

Mistakes and changes are reserved.

MC92 Terminal

Variants/Accessories

Variants		Part-No.
MC92 Terminal		162503
MC92 Terminal	with USB	162216
MC92 Terminal	with USB + GPS	162202

Accessories	Description	Part-No.
Top-hat rail power supply	12VDC with Phoenix connector	100909
Power supply	EU approval, Input: 100 - 240 V AC, Output 24 V DC / 1.0A	100877
Serial data cable	RS232 Sub D9 (female) with 3pin plug, 1 m	162500
USB Cable	A/B, 1 m	100897
USB Cable	A/B, 1,8 m	100898
Portable antenna	GSM/UMTS/WLAN/LTE, bendable, 163 x 22 x 7 mm, SMA (male)	101292
Portable LTE-MIMO antenna	Desk/window mount, GSM/UMTS/LTE, 2 x 2m RG174 SMA (male)	101268
Magnetic base antenna	GSM/UMTS/LTE, 3 m RG174 SMA (male), Ø 31 x 72 mm	101296
Omnidirectional antenna	Wall mounting (indoor/outdoor), GSM/ISM/UMTS/LTE, length 269 mm, 5m CFD195 low loss SMA (male)	100966
Omnidirectional antenna	Screw mounting, GSM/GPS/UMTS/LTE, 2 x 3 m RG174 SMA (male)	101033